

BLANK PAGE



IS 4696 (Part 2): 2004

भारतीय मानक मीट्रिक बट्रैस चूड़ियों के लिए आयाम भाग 2 चूड़ी-अन्तराल व्यास संचयन (दूसरा पुनरीक्षण)

Indian Standard

DIMENSIONS FOR METRIC BUTTRESS THREADS

PART 2 PITCH DIAMETER COMBINATIONS

(Second Revision)

ICS 21.040.10

© BIS 2004

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (Part 2) (Second Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Engineering Standards Sectional Committee had been approved by the Medical Instruments, General and Production Engineering Division Council.

This standard was first published in 1968 and subsequently revised in 1976 splitting up into four parts. The other parts in this series are:

(Part 1): 1976 Basic and design profile

(Part 3): 1976 Basic dimensions (Part 4): 1976 Tolerancing system

The title of the standard in general has also been modified in line with DIN 513.

The earlier edition of this standard (Part 2) was in line with DIN 513 (Part 2)-1975. In the preparation of this revision considerable assistance has been derived from latest edition of DIN 513 Sheet 2-1985 'Metrisches Sägengewinde, Gewindereihen (Metric buttress threads, general plan)', issued by DIN, Deutsches Institut für Normung and has been brought in line with it.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2: 1960 'Rules for rounding off the numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

DIMENSIONS FOR METRIC BUTTRESS THREADS

PART 2 PITCH DIAMETER COMBINATIONS

(Second Revision)

1 SCOPE

This standard (Part 2) covers a series of pitch and diameter combinations for metric buttress threads in the diameter range of M 10 to M 640 mm.

2 DIAMETERS AND PITCHES

2.1 The order of preference for selection of diameters and pitches shall be as follows.

2.1.1 Diameters

- a) First choice diameters,
- b) Second choice diameters, and
- c) Third choice diameters.

2.1.2 Pitches

Pitches in boxes shall be preferred.

2.2 If pitches other than indicated in Table 1 are required, one of the pitches associated with the next higher diameter may be chosen. In any case, third choice diameter shall not be used for new design.

3 PITCH DIAMETER COMBINATIONS

The pitch diameter combination shall be as given in Table 1.

4 DESIGNATIONS

4.1 Single start metric buttress threads conforming to this standard shall be designated by the letter 'ST' followed by the value of the nominal diameter and pitch expressed, in millimetres, and separated by the sign 'x'1).

Example:

Single start threads of nominal diameter 40 mm and pitch 7 mm shall be designated as:

4.2 Multiple start metric buttress threads conforming to this standard shall be designated by the letter 'ST' followed by the value of the nominal diameter and lead of the multiple start threads, separated by the sign 'x' and in brackets the letter 'P' and the value of the pitch (diameter between two neighbouring ridges), all expressed in millimetres.

Example:

Double start threads of nominal diameter 40 mm, lead 14 mm and pitch 7 mm shall be designated as:

$$ST 40 \times 14 (P 7)$$

(Numbers of starts = $\frac{\text{Lead}}{\text{Pitch}} = \frac{14}{7}$ defines a screw thread of 40 diameter with 2 Start).

For buttress threads with no tolerance indication, the medium tolerance quality shall apply (tolerance zone 7e for external threads and 7H for internal threads. If a different tolerance zone is required, this shall be indicated; the designation for external threads of tolerance zone 8e shall then be read as 'ST 40 × 7 - 8e'.

Table 1 Pitch Diameter Combinations for Metric Buttress Threads

(Clauses 2.2 and 3)

All dimensions in millimetres.

Nominal Diameter, d Pitches																							
	Second Choice		44	40	36	32	28	24	22	20	18	16	14	12	10	9	8	7	6	5	4	3	2
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)	(23)	(24)
10 12	14																				•	3	2 2 2
16 20	18																		-		4 4		2 2 2
24	22 26																8 8 8			5 5 5		3 3 3	
28	30														10 10		8		6	5		3 3	
36	34														10 10 10			7	6			3 3 3	
40	42													12	10 10			7 7 7		-		3 3 3	
48	46													12 12 12			8 8 8	,				3 3 3	
52	55												14	12		9	8					3	
60	65											16	14		10	9					4	3	
70	75											16 16			10 10						4 4		
90	85					-					18 18	10		12	10						4 4		
100	95	105								20 20	18			12 12 12			1				4 4 4		
120	110	115							22 22	20			14	12					6		4		
	130	125						24	22 22				14 14 14						6 6 6				
140	150	145						24 24 24				16	14 14						6 6				
160		155					28	24				16 16 16							6 6 6				

Table 1 (Concluded)

															(4.6)	(1.5)	(10)	(10)	(20)	(2.1)	(22)	(22)	(24)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)		(14)	(15)	(16)	(17)	(18)	(19)		(21)	(22)	(23)	(24)
	170						28					16							6				
180		175		l			28					16					8						
							28				18						8						
		185				32					18						8						
	190					32					18						8						
· 		195				32					18						8						
200						32					18						8						
i	210				36					20							8						
220					36					20							8						
	230		Н		36					20							8						
240					36				22							ĺ	8						
	250			40					22					12									
260				40					22					12								1	
	270			40				24					ļ	12									
280				40				24						12								<u> </u>	
	290		44					24						12									
300			44		i			24						12						ļ			j '
	320		44				ľ							12	1				1				
340			44			·								12									
	360													12					l				
380											ŧ		ĺ	12		ł						ŀ	
	400				<u> </u>			1	-			1		12		1			i				
420											18						1						
	440							İ	ļ		18								1				
460					_	T	\vdash	t —			18	1											
ŀ	480			İ							18										1	1	
500			İ					İ			18												
	520				t	†	T	24			1		t		1		<u> </u>						Τ
540							İ	24										1					
ļ	560							24							1			1					
580			 	\vdash		1.	†	24	1	T	1		!		T		1	1	T			1	
	600							24											1				
620								24															
	640							24															

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publication), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc: No. BP 20 (0464).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
		,

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephone	es: 2323 0131, 2323 3375, 2323 9402	website: www.bis.org.in	
Regional	Offices:		Telephones
Central	: Manak Bhavan, 9 Bahadur Shah Zafar Mar NEW DELHI 110002	,	2323 7617 2323 3841
Eastern	: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Ka KOLKATA 700054	nkurgachi { 2337 8499 2337 8626	, 2337 8561 , 2337 9120
Northern	: SCO 335-336, Sector 34-A, CHANDIGAR	H 160022	$\begin{cases} 260\ 3843 \\ 260\ 9285 \end{cases}$
Southern	: C.I.T. Campus, IV Cross Road, CHENNAI	600113 {2254 1216 2254 2519	, 2254 1442 , 2254 2315
Western	: Manakalaya, E9 MIDC, Marol, Andheri (E	sst) \$\int 2832 9295 \\ 2832 7891	, 2832 7858 . 2832 7892

Branches: AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD.

GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM.